


OPTION INSTANTANEOUS RELAY

Product	Option L for D-U200 series						Country of Origin: The Netherlands
Description	Equiped with LED for signalling of voltage presence on the coil.						Company
							
						P.O. Box 7023 3502 KA Utrecht The Netherlands T +31 (0)30-288 13 11 F +31 (0)30-289 88 16 E sales@nieaf-smitt.nl I www.nieaf-smitt.nl/railway	
Coil data							
Type	U_{nom}	U_{min}	U_{max}	U_{drop-out}	R_{coil}	I_{coil-nom}	
D-U201-L	24 VDC	16.8 VDC	30 VDC	2.5 VDC	270 Ω	88.9 mA	
D-U202-L	48 VDC	33.6 VDC	60 VDC	4.8 VDC	936 Ω	51.3 mA	
D-U203-L	72 VDC	50.4 VDC	90 VDC	13 VDC	2406 Ω	29.9 mA	
D-U204-L	110 VDC	77 VDC	137.5 VDC	11 VDC	5250 Ω	21.0 mA	
D-U205-L	96 VDC	67 VDC	120 VDC	9.5 VDC	3531 Ω	27.2 mA	
D-U207-L	36 VDC	25.2 VDC	45 VDC	3.5 VDC	562 Ω	64.1 mA	
Other coil data		Dimensions			Contact data		
As standard D-U200 relay		As standard D-U200 relay			As standard D-U200 relay		